SAFETY DATA SHEET



Section 1. Identification

Product name Brayco Micronic 815 Z Distributor: SPI Supplies / Structure Probe Inc.

SDS # 459679

West Chester, PA 19380

Code 459679-US03 Phone: 610-436-5400; 1-800-242-4774

Fax: 610-436-5755

206 Garfield Avenue

Email: sales@2spi.com

Relevant identified uses of the substance or mixture and uses advised against

SPI Catalog #s: 06014-AB, 06014-XQ

Product use Lubricant

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Supplier BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: +1-888-CASTROL

EMERGENCY HEALTH

INFORMATION:

+1-800-447-8735

EMERGENCY SPILL +1-800-424-9300 (CHEMTREC USA)

INFORMATION: +1-703-527-3887 (CHEMTREC outside the US)

Section 2. Hazards identification

OSHA/HCS status This material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Classification of the

substance or mixture

Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Hazards not otherwise Defatting to the skin.

classifiedThermal degradation products may include hydrogen fluoride gas. Possibility of

corrosive damage from hydrofluoric acid and systemic fluoride toxicity should be

considered where exposure has occurred to such degradation products.

Section 3. Composition/information on ingredients

Substance/mixture Substance

Fluorochemical derivative.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name Brayco Micronic 815 Z Product code 459679-US03 Page: 1/9

Version 5.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 4. First aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and

remove any contact lenses. Get medical attention.

Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove Skin contact

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly

before reuse. Get medical attention if symptoms occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Specific treatments No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Do not use water jet.

Specific hazards arising from the chemical

Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if they come into contact with red hot swarf. To minimise the generation of red hot swarf ensure that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flood it throughout cutting operations. As an additional precaution swarf should be regularly cleared from the immediate area to prevent the risk of fire. In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

Combustion products may include the following:

halogenated compounds

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions

for fire-fighters

Special protective equipment for fire-fighters

Special remarks on fire

hazards

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA)

and full turnout gear.

Hazardous decomposition products: Hydrogen fluoride (HF), and Carbonyl fluoride

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-

emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Product code 459679-US03 Product name Brayco Micronic 815 Z Page: 2/9

Version 5.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Concentrations of mist, fumes and vapors in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Avoid excessive heat.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

This product does not have any assigned OELs.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Product nameBrayco Micronic 815 ZProduct code459679-US03Page: 3/9

Version 5.02 **Date of issue** 12/19/2023.

Format US

Language ENGLISH

Section 8. Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection
Skin protection
Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Butyl gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3).

Where organic vapours are a potential hazard during metalworking operations, a

combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state
Color
Color
Colorless.

Odor
Not available.

Odor threshold
PH
Not applicable.

Melting point/freezing point
Not available.

Product nameBrayco Micronic 815 ZProduct code459679-US03Page: 4/9

Version 5.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 9. Physical and chemical properties

Boiling point, initial boiling point, and boiling range

Not available.

Flash point Not available.

None.

-40 °C **Pour point**

Evaporation rate Not available.

Flammability

Lower and upper explosion limit/flammability limit

Not applicable. Based on - Physical state

Not available.

Vapor pressure Not available.

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapor density Not available.

Density >1000 kg/m3 (>1 g/cm3) at 20°C

Solubility(ies)

Media	Result
W ater	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Kinematic: 155 mm²/s (155 cSt) at 40°C

VOC 1 g/l

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid Avoid excessive heat.

Active metals, metal oxides at temperatures > 280 C, Lewis acid catalysts, strong or non-Incompatible materials

aqueous alkali.

Hazardous decomposition

products

When conditions to avoid and/or incompatible materials are met, the following decomposition products may occur: carbonyl difluoride, hydrogen fluoride (HF)

Product code 459679-US03 Product name Brayco Micronic 815 Z Page: 5/9

Version 5.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 11. Toxicological information

Information on toxicological effects

Information on the likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact No known significant effects or critical hazards. Skin contact No known significant effects or critical hazards.

Inhalation Vapor inhalation under ambient conditions is not normally a problem due to low vapor

pressure.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Skin contact Adverse symptoms may include the following:

> irritation dryness cracking

Inhalation No specific data. Ingestion No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Potential chronic health effects

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. No known significant effects or critical hazards. **Fertility effects**

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Inhalation of decomposition products (occurs if heated > 260 C) or of smoke from **Additional information**

contaminated tobacco products may cause respiratory irritation and induce Polymer Fume Fever condition. Symptoms of exposure to decomposition products are: lung

irritation, pulmonary edema, flu-like symptoms (example - fever chills).

Product code 459679-US03 Page: 6/9 Product name Brayco Micronic 815 Z Format US Language ENGLISH

Version 5.02 Date of issue 12/19/2023.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility Liquid. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments

Not available.

Product nameBrayco Micronic 815 ZProduct code459679-US03Page: 7/9Version 5.02Date of issue 12/19/2023.Format USLanguage ENGLISH

Section 15. Regulatory information

U.S. Federal regulations

United States inventory

(TSCA 8b)

All components are active or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification Not applicable.

SARA 313

Form R - Reporting This product does not contain any hazardous ingredients at or above regulated

thresholds. requirements

This product does not contain any hazardous ingredients at or above regulated Supplier notification

thresholds.

State regulations

Massachusetts None of the components are listed. **New Jersey** None of the components are listed. **Pennsylvania** None of the components are listed.

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Other regulations

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** All components are listed or exempted.

(PICCS)

Taiwan Chemical All components are listed or exempted.

Substances Inventory

(TCSI)

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with

the current requirements of REACH.

Section 16. Other information

National Fire Protection Association (U.S.A.)



A NFPA health hazard rating of "3" is assigned due to toxicity of thermal decomposition products and fluorine (HF); otherwise, the material itself warrants a health hazard rating of "1".

History

12/19/2023. Date of issue/Date of

revision

05/30/2022. Date of previous issue

Prepared by Product Stewardship

Product code 459679-US03 **Product name** Brayco Micronic 815 Z Page: 8/9

Version 5.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 16. Other information

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet

STEL = Short term exposure limit TWA = Time weighted average

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Brayco Micronic 815 Z Product code 459679-US03 Page: 9/9

Language ENGLISH