Material Safety Data Sheet



1. Product and company identification

Product name Optitool 215-2

MSDS # 459656 Historic MSDS #: 25097-AE Code 459656-US03

Product use Lubricant Grease

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer Castrol Industrial North America, Inc.

150 W. Warrenville Road Naperville, IL 60563

Supplier Castrol Industrial North America, Inc.

150 W. Warrenville Road Naperville. IL 60563

Product Information: +1-877-641-1600

EMERGENCY SPILL INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

2. Hazards identification

Physical state Grease

Color Off-white.

Emergency overview CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes May cause eye irritation.

Skin May cause skin irritation.

Inhalation May cause respiratory tract irritation.

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

3. Composition/information on ingredients

This product does not contain any hazardous ingredients at or above regulated thresholds.

Product nameOptitool 215-2Product code459656-US03Page: 1/5Version 1.01Date of issue11/09/2010.Format USLanguage ENGLISH.

(US) (ENGLISH)

4. First aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if symptoms occur.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash

clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms

occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

Note: High Pressure Applications Notes to physician

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue

becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along

tissue planes.

5. Fire-fighting measures

Fire/explosion hazards In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Do not use water jet.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Fire-fighting procedures

No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion

products

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO2 etc.)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures

Personal precautions No action shall be taken involving any personal risk or without suitable training. Keep unnecessary

and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see

section 8).

Environmental Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, precautions

waterways, soil or air).

Methods for cleaning up

Small spill

Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent

entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Product code

Note: see section 1 for emergency contact information and section 13 for waste disposal.

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if watersoluble or absorb with an inert dry material and place in an appropriate waste disposal container.

Dispose of via a licensed waste disposal contractor.

Product name Optitool 215-2

Language ENGLISH. Version 1.01 Date of issue 11/09/2010. **Format US**

> (US) (ENGLISH)

459656-US03

Page: 2/5

7. Handling and storage

Handling Put on appropriate personal protective equipment (see section 8). Workers should wash hands

and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate

respirator when ventilation is inadequate.

Storage Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-

ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate

containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Some states may enforce more stringent exposure limits.

Control Measures

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

reusing.

Personal protection

Eyes Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory Use adequate ventilation. In accordance with good industrial hygiene and safety work practices,

airborne exposures should be controlled to the lowest extent practicable.

HandsThe correct choice of protective gloves depends upon the chemicals being handled, the conditions

of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

9. Physical and chemical properties

Physical state Grease
Color Off-white.
Odor Mild.

Density 860 kg/m³ (0.86 g/cm³) at 15.6°C

Solubility insoluble in water.

10. Stability and reactivity

Stability and reactivity The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition Unde

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product nameOptitool 215-2Product code459656-US03Page: 3/5Version 1.01Date of issue11/09/2010.Format USLanguage ENGLISH.(US)(ENGLISH)

Hazardous polymerization

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Other information

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

Mobility Non-volatile. Grease. insoluble in water.

13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Optitool 215-2: Immediate (acute) health hazard

immediate (acute) nealth naza

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4): CERCLA: Hazardous substances.: 4,4'-diaminodiphenylmethane: 10 lbs. (4.54 kg);

•

State regulations

Massachusetts None Substances

None of the components are listed.

Product name Optitool 215-2Product code 459656-US03 Page: 4/5Version 1.01Date of issue 11/09/2010.Format US (US)Language ENGLISH.

New Jersey Hazardous None of the components are listed.

Pennsylvania RTK

None of the components are listed. **Hazardous Substances**

California Prop. 65 WARNING: This product contains a chemical known to the State of California to cause cancer.

4,4'-diaminodiphenylmethane

Inventories

Substances

Canada inventory At least one component is not listed. **Europe inventory** All components are listed or exempted. **Australia inventory (AICS)** At least one component is not listed. China inventory (IECSC) At least one component is not listed.

Japan inventory (ENCS) At least one component is not listed.

Korea inventory (KECI) At least one component is not listed.

Philippines inventory At least one component is not listed.

(PICCS)

16. Other information

Label requirements CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

HMIS® Rating: Health **National Fire Protection Flammability**

Physical Hazard Personal R protection

Association (U.S.A.)



Other special considerations

History

Date of issue 11/09/2010. Date of previous issue 04/21/2010.

Prepared by Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name Optitool 215-2 **Product code** 459656-US03 Page: 5/5 Language ENGLISH. Version 1.01 Date of issue 11/09/2010. **Format US** (US) (ENGLISH)