# **Material Safety Data Sheet**



## 1. Product and company identification

Braycote Micronic 600 EF **Product name** 

MSDS# 459633 **Historic MSDS #:** 25031-AE Code 459633-US03

**Product use** Lubricant

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer Castrol Industrial North America, Inc.

> 150 W. Warrenville Road Naperville, IL 60563

Supplier Castrol Industrial North America, Inc.

> 150 W. Warrenville Road Naperville, IL 60563

Product Information: +1-877-641-1600

**EMERGENCY SPILL INFORMATION:** 

1 (800) 424-9300 CHEMTREC (USA)

#### 2. Hazards identification

Physical state Grease Color Off-white. **Emergency overview** CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

**Eyes** May cause eye irritation. Skin May cause skin irritation.

Inhalation May cause respiratory tract irritation.

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

## 3. Composition/information on ingredients

This product does not contain any hazardous ingredients at or above regulated thresholds.

#### 4. First aid measures

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical **Eye contact** 

attention if symptoms occur.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash

clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms

occur.

Product name Braycote Micronic 600 EF **Product code** 459633-US03 Page: 1/5 Language ENGLISH. **Version** 2.01 **Date of issue** 10/14/2010. **Format US** 

> (US) (ENGLISH)

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

Notes to physician Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue

becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along

tissue planes.

## 5. Fire-fighting measures

Fire/explosion hazards No specific fire or explosion hazard.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Do not use water jet.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Fire-fighting procedures

No action shall be taken involving any personal risk or without suitable training.

**Hazardous combustion** 

products

Combustion products may include the following: halogenated compounds

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire

hazards

Hazardous decomposition products: Hydrogen fluoride (HF), and carbonyl fluoride.

#### Accidental release measures

Personal precautions No action shall be taken involving any personal risk or without suitable training. Keep unnecessary

and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on

appropriate personal protective equipment (see section 8).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. **Environmental** precautions

Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods for cleaning up

Large spill Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1

for emergency contact information and section 13 for waste disposal.

Small spill Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled

waste container. Dispose of via a licensed waste disposal contractor.

## Handling and storage

Handling Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is

inadequate.

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-Storage ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate

containment to avoid environmental contamination.

Product name Braycote Micronic 600 EF

**Product code** 

459633-US03

Page: 2/5

**Version** 2.01 **Date of issue** 10/14/2010.

**Format US** 

Language ENGLISH.

(US)

(ENGLISH)

### 8. Exposure controls/personal protection

#### Occupational exposure limits

Some states may enforce more stringent exposure limits.

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, Control Measures

use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Wash hands, forearms and face thoroughly after handling chemical products, before eating, **Hygiene measures** 

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

Personal protection

Eves Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body Avoid contact with skin and clothing. Wear suitable protective clothing.

Use adequate ventilation. Avoid breathing dust. Respiratory

**Hands** The correct choice of protective gloves depends upon the chemicals being handled, the conditions

> of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

### 9. Physical and chemical properties

Grease Physical state Color Off-white. Odor Odorless.

1900 kg/m3 (1.9 g/cm3) at 15.6°C **Density** 

insoluble in water. Solubility

#### 10. Stability and reactivity

Stability and reactivity The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatibility with

various substances

Reactive or incompatible with the following materials: Alkali metals and halogenated compounds.

Strong Alkali or Lewis acids at high temperature.

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

Hazardous polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11. Toxicological information

Other Toxicity Data Decomposition products thermal decomposition may release hazardous gases. Hydrogen fluoride

(HF). Inhalation of decomposition products (occurs if heated > 260 C) or of smoke from contaminated tobacco products may cause respiratory irritation and induce Polymer Fume Fever condition. Symptoms of exposure to decomposition products are: lung irritation, pulmonary

edema, flu-like symptoms (example - fever chills).

Other information

Potential chronic health effects

Product name Braycote Micronic 600 EF **Product code** 459633-US03 Page: 3/5 Version 2.01 Date of issue 10/14/2010. Format US Language ENGLISH. (US) (ENGLISH)

## 12. Ecological information

#### **Ecotoxicity**

No testing has been performed by the manufacturer.

### 13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

### 15. Regulatory information

#### U.S. Federal Regulations

**United States inventory** (TSCA 8b)

All components are listed or exempted.

TSCA 12(b) one-time export: Polytetrafluoroethylene

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Braycote

Micronic 600 EF: Immediate (acute) health hazard

**SARA 313** 

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

**Supplier notification** 

This product does not contain any hazardous ingredients at or above regulated thresholds.

**CERCLA Sections** 102a/103 Hazardous Substances (40 CFR

CERCLA: Hazardous substances.: No products were found.

Part 302.4): State regulations

> **Massachusetts Substances**

None of the components are listed.

**New Jersey Hazardous Substances** 

None of the components are listed.

Pennsylvania RTK **Hazardous Substances**  The following components are listed: ETHENE, TETRAFLUORO-, HOMOPOLYMER

California Prop. 65

California Prop 65: No products were found

**Inventories** 

**Canada inventory** At least one component is not listed.

Product name Braycote Micronic 600 EF **Product code** 459633-US03 Page: 4/5 Language ENGLISH. Version 2.01 Date of issue 10/14/2010. **Format US** (US) (ENGLISH) Europe inventory

Australia inventory (AICS)

China inventory (IECSC)

Japan inventory (ENCS)

Korea inventory (KECI)

Philippines inventory
(PICCS)

All components are listed or exempted.

#### 16. Other information

Label requirements CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Fire hazard

Health

Instability

Specific hazard

HMIS® Rating: Health 1 National Fire

Flammability 1 Protection
Physical 0 Association (U.S.A.)

Hazard Personal B protection

Other special

A NFPA health hazard rating of "3" is assigned due to toxicity of thermal decomposition products

considerations and fluorine (HF); otherwise, the material itself warrants a health hazard rating of "1".

Date of issue 10/14/2010.

Date of previous issue 05/20/2010.

Prepared by Product Stewardship

Notice to reader

**History** 

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product nameBraycote Micronic 600 EFProduct code459633-US03Page: 5/5Version 2.01Date of issue 10/14/2010.Format USLanguage ENGLISH.(US)(ENGLISH)