



**CARGILLE LABORATORIES, INC.**

55 Commerce Road • Cedar Grove, New Jersey • 07009-1289 USA  
Phone: 973-239-6633 Fax: 973-239-6096 Email: CargilleLabs@aol.com URL: http://www.cargille.com

**CATALOG #19569, 19570**

IDENTITY ( AS USED ON LABEL AND MANUF. LITERATURE ) <b>CARGILLE IMMERSION LIQUID  CODE 50350</b>	NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.
---	---

**SECTION 1**

MANUFACTURER'S NAME CARGILLE LABORATORIES, INC.	EMERGENCY TELEPHONE NUMBER WEEKDAY 973 - 239 - 6633 24 HR CHEMTREC 800 - 424 - 9300	
ADDRESS ( NUMBER, STREET, CITY, STATE, AND ZIP CODE )	TELEPHONE NUMBER FOR INFORMATION 973 - 239 - 6633	
55 COMMERCE ROAD	DATE PREPARED MAY 23, 2011	SUPERCEDES PRIOR DATED MSDS FOR THIS MATERIAL
CEDAR GROVE, NJ 07009	SIGNATURE OF PREPARER ( OPTIONAL )	
THE INFORMATION SUPPLIED IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION PRESENTED AND CARGILLE LABORATORIES ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF THE USE OF THIS PRODUCT. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RESPONSIBLE FOR ITS USE SHALL MAKE HIS OR HER OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS OR HER PARTICULAR PURPOSE.		
<u>C</u> ONDITIONS OF <u>I</u> NTENDED AND <u>N</u> ORMAL <u>U</u> SE: ( ABBR. C.I.U. ) AS AN OPTICAL IMMERSION LIQUID AT NORMAL ROOM <u>P</u> RESSURE ( 760 mm Hg ), <u>T</u> EMPERATURE 39 °F TO 150 °F IN A NON MISTED / NON AIRBORN <u>S</u> TATE IN A ROOM HAVING NORMAL AIR CHANGES ( 2 ) / HR., IN A TRAINED AND SUPERVISED LABORATORY / INDUSTRIAL SETTING USING STANDARD GL / GM PROCEDURES. SEE SECTIONS 7 AND 8		

**SECTION 2 - HAZARDOUS INGREDIENTS**

**SPECIFIC CHEMICAL IDENTITY INFORMATION**

HAZARDOUS COMPONENTS	( COMMON NAME ( S ) )	OSHA PEL CEILING	ACGIH TLV T.W.A.	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
TRADE SECRET	ALIPHATIC / ALICYCLIC HYDROCARBONS	5 mg / CUBIC METER *	N.D.F.		

\*PEL CEILINGS & TLV T.W.A.s IF ANY SHOULD NOT OCCUR IF C.I.U. AND SECTIONS 7 & 8 FOLLOWED.

NOTE: PRODUCT NORMALLY SOLD IN 4 OZ. TO 5 GALLON.QUANTITIES. USED IN SINGLE DROP TO A FEW CUBIC CENTIMETERS PER APPLICATION. SEE REQUISITIONER FOR SPECIFIC QUANTITIES INVOLVED.

**SECTION 3 - PHYSICAL / CHEMICAL CHARACTERISTICS**

BOILING POINT AT 760 mm Hg > 230 °C	> 450 °F	SPECIFIC GRAVITY ( H <sub>2</sub> O = 1 ) TEMP. 23 °C / 73 °F	< 1.0
VAPOR PRESSURE IN mm Hg ( TEMP. ) 73 °F	< .5	MELTING POINT	< 32 °F
VAPOR DENSITY ( AIR = 1 ) AT (mm Hg & TEMP. ) 760 73 °F	ca 1	EVAPORATION RATE AT 760 mm Hg & 23 °C / 73 °F ( MINERAL OIL = 1 )	ca 1
SOLUBILITY IN WATER AT (mm Hg & TEMP. ) 760 73 °F	NIL	APPEARANCE AND ODOR WATER WHITE, NO TASTE OR ODOR	

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT ( CUP METHOD USED ) > 250 °F ( 120 °C ) C.O.C.	FLAMMABLE LIMITS	LEL N.D.F.	UEL N.D.F.
EXTINGUISHING MEDIA TREAT AS PETROLEUM GREASE FIRE, USE FOAM OR DRY CHEMICAL / ANY CLASS B AGENT			
SPECIAL FIRE FIGHTING PROCEDURES NONE			
UNUSUAL FIRE AND EXPLOSION HAZARDS NONE			

ABBREVIATIONS: N.A. = NOT APPLICABLE; N.D.F. = NO DATA FOUND; TR.S. = TRADE SECRET; N.E. = NOT ESTABLISHED;  
C.I.U. = CONDITIONS OF INTENDED USE; < = LESS THAN; > = GREATER THAN.

<b>SECTION 5 - REACTIVITY DATA</b>				
STABILITY	UNSTABLE		N.A.	
	STABLE	YES		
INCOMPATIBILITY ( MATERIALS AND / OR CONDITIONS TO AVOID ) STRONG OXIDIZERS, HEAT ABOVE 150 °F				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	
	WILL NOT OCCUR	X	N.A.	
<b>SECTION 6 - HEALTH HAZARD DATA</b>				
ROUTE ( S ) OF ENTRY: ( NOT LIKELY AT C.I.U. )	INHALATION? YES	SKIN? SLIGHT	MUCOUS MEMBRANES / EYES? SLIGHT	INGESTION? POSSIBLE
HEALTH HAZARDS ( ACUTE AND CHRONIC ) NONE KNOWN AT C.I.U.				
CARCINOGENICITY LISTED:	NTP? NO	IARC MONOGRAPHS? NO	OSHA CARCINOGEN? NO	
SIGNS AND SYMPTOMS OF EXPOSURE OILY FEEL, IF LIQUID IS MISTED OR ABOVE 150 °F ( NOT A C.I.U. ) HEADACHES AND NAUSEA POSSIBLE.				
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE N.D.F.				
EMERGENCY AND FIRST AID PROCEDURES: INCLUDE POSSIBLE MATERIAL THAT MAY HAVE BEEN MIXED WITH LIQUID DURING USE. INHALATION – ( NOT LIKELY AT C.I.U. ) IF CONCERN ARISES, REMOVE TO FRESH AIR.				
SKIN & CLOTHES – PROMPT SOAP AND WATER WASH.				
EYE - FLUSH WITH WATER, SLIGHT TEMPORARY IRRITATION POSSIBLE ( CONSULT PHYSICIAN ).				
INGESTION – LOW ORDER OF TOXICITY, FIRST AID NORMALLY NOT NEEDED ( CONSULT PHYSICIAN ).				
<b>SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE – FOLLOW C.I.U. SEE SECTION 1</b>				
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED ABSORB, PLACE IN PLASTIC ( POLYETHYLENE OR POLYPROPYLENE ) CONTAINER, CAP OR TWIST TIE CLOSURE ( SEE SECTION 8 )				
WASTE DISPOSAL METHOD: ALL CHEMICAL DISPOSALS MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE, AND FEDERAL REGULATIONS.				
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE BETWEEN 65 °F AND 90 °F ( 18 °C AND 32 °C )				
OTHER PRECAUTIONS AVOID CONTINUAL DIRECT SUNLIGHT.				
<b>SECTION 8 - CONTROL MEASURES; WHEN USED AS INTENDED ( SEE SECTION 1 )</b>				
RESPIRATORY PROTECTION ( SPECIFY TYPE ) SEE "VENTILATION"				
VENTILATION	LOCAL EXHAUST *	SPECIAL	NONE	
	MECHANICAL ( GENERAL ) *	OTHER	N.A.	
PROTECTIVE GLOVES * IF WORN, POLYETHYLENE GLOVES ARE RECOMMENDED	EYE PROTECTION *			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT N.A.				
* = NOT MANDATORY EXCEPT AS GOOD LABORATORY INDUSTRIAL PRACTICES. ALWAYS USE GOOD HYGIENIC WORK / PRACTICES AS TO HOUSEKEEPING, PERSONAL HYGIENE, USE OF CHEMICAL LAB APRON AND SPLASH GOGGLES, AVOIDANCE OF VAPORS, PROLONGED AND REPEATED SKIN CONTACT.				
SPECIAL PRECAUTIONS N.A.				